



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/759,153	01/16/2001	Ghassan Naim	59864.00548	2840
32294 7590 06/26/2007 SQUIRE, SANDERS & DEMPSEY L.L.P. 14TH FLOOR 8000 TOWERS CRESCENT TYSONS CORNER, VA 22182			EXAMINER NGUYEN, TOAN D	
			ART UNIT 2616	PAPER NUMBER
			MAIL DATE 06/26/2007	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

09/759,153

Applicant(s)

NAIM ET AL.

Examiner

Toan D. Nguyen

Art Unit

2616

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 06 April 2007.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-19 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-19 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 06 July 2001 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
 - ☐ Certified copies of the priority documents have been received in Application No. _____.
 - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- ☐ Notice of References Cited (PTO-892)
- ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____
- ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____
- ☐ Notice of Informal Patent Application (PTO-152)
- ☐ Other: _____

DETAILED ACTION

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

3. Claims 1-7, and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hwang et al. (EP 0981229 A2) in view of Yao et al. (US 6,785,262).

For claims 1, 2, 7 and 16, Hwang et al. disclose controlling asymmetric dynamic radio bearers in mobile packet data communications system, comprising:

monitoring the length of data queue in the first network elements as an indication of future need of communication resources in a first network element (figure 1, Abstract lines 14-16, and page 3, col. 4 lines 18-25);

sending the indication from the first network element (page 3, col. 4 lines 18-25 and col. 4 lines 51-53);

controlling the communication resources between the first network element and a second network element based on this indication (Abstract lines 1-9, page 2, col. 2 line 18 to page 3 line 1); and

controlling communications resources in a transmission from the first network element to the second network element (Abstract lines 1-9, page 2, col. 2 line 18 to page 3 line 1).

However, Hwang et al. do not expressly disclose a controller, wherein the communication resources are allocated, and wherein the indication is a coded value of a length of a data queue. In an analogous art, Yao et al. disclose a controller, wherein the communication resources are allocated (figure 3, reference 14, col. 6 line 55), and wherein the indication is a code value (col. 9 lines 57-59) of a length of the data queue (col. 12 lines 6-8, and col. 12 lines 41-43).

Yao et al. disclose further wherein the first network element (figure 3, reference 10) is connected to the controller (figure 3, reference 14, col. 6 lines 54-55) by way of the second network element (figure 3, reference 12)(col. 7 lines 27-28 as set forth in claim 2); wherein in the monitoring, the first network element is a mobile station (figure 3, reference 10) and the second network element is a base station (figure 3, reference 12) of a wireless communication network (col. 7 lines 27-28 as set forth in claim 7), and wherein sending step further comprises sending the indication of the length of the data queue is sent in every packet (col. 9 lines 58-60 as set forth in claim 16).

Art Unit: 2616

One skilled in the art would have recognized the controller, wherein the communication resources are allocated, and wherein the indication is a coded value of the length of the data queue, and would have applied Yao et al.'s determine the channel quality based on the length of queue 408 in Hwang et al.'s mobile station transmission. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention, to use Yao et al.'s method and apparatus for voice latency reduction in a voice-over-data wireless communication system in Hwang et al.'s controlling asymmetric dynamic radio bearers in mobile packet data communications system with the motivation being to determine channel quality (col. 12 line 1).

For claim 3, Hwang et al. disclose wherein in the sending, the indication includes information about a transmit buffer of the first network element (page 2, col. 2 lines 23-44).

For claim 4, Hwang et al. disclose wherein in the sending, the indication includes information on the additional resources needed for said first network element (figure 4, page 2, col. 2 lines 28-34, and page 5, col. 7 lines 9-36).

For claim 5, Hwang et al. disclose controlling asymmetric dynamic radio bearers in mobile packet data communications system, comprising:

monitoring an indication of future need of communication resources in a first network element (figure 1, page 3, col. 4 lines 18-25);

sending the indication from the first network element (page 3, col. 4 lines 18-25, and col. 4 lines 51-53);

controlling the communication resources between the first network element and a second network element based on this indication (Abstract lines 1-9, page 2, col. 2 line 18 to page 3 line 1), and

controlling communications resources in a transmission from the first network element to the second network element (Abstract lines 1-9, page 2, col. 2 line 18 to page 3 line 1),

wherein the indication includes information about a transmit buffer of the first network element (figure 4, page 2, col. 2 lines 28-34, and page 5, col. 7 lines 9-36).

However, Hwang et al. do not expressly disclose a controller, wherein the communication resources are allocated, and wherein the controller is separate and independent from the first network element, wherein the indication includes coded value corresponding to predefined resources. In an analogous art, Yao et al. disclose a controller, wherein the communication resources are allocated (figure 3, reference 14, col. 6 line 55), and wherein the controller (figure 3, reference 14, col. 6 lines 54-55) is separate and independent from the first network element (figure 3, reference 10)(col. 7 lines 27-31), wherein the indication includes coded value (col. 9 lines 57-59) corresponding to predefined resources (col. 12 lines 6-13).

One skilled in the art would have recognized the controller, wherein the communication resources are allocated and wherein the controller is separate and independent from the first network element, wherein the indication includes coded value corresponding to predefined resources, and would have applied Yao et al.'s determine the channel quality based on the length of queue 408 in Hwang et al.'s mobile station

transmission. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention, to use Yao et al.'s method and apparatus for voice latency reduction in a voice-over-data wireless communication system in Hwang et al.'s controlling asymmetric dynamic radio bearers in mobile packet data communications system with the motivation being to determine channel quality (col. 12 line 1).

For claim 6, Hwang et al. disclose wherein in the monitoring, the indication includes information about a transmit buffer of the first network element (figure 4, page 2, col. 2 lines 28-34, and page 5, col. 7 lines 9-36).

4. Claims 8-10, 12-13, and 17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yao et al. (US 6,785,262) in view of Hwang et al. (EP 0981229 A2).

For claim 8, Yao et al. disclose method and apparatus for voice latency reduction in a voice-over-data wireless communication system, comprising:

a plurality of first stations (figure 3, reference 10, col. 7 line 2);

a second station (figure 3, reference 12) connected to said plurality of first stations (figure 3, reference 10) through a plurality of communication links (col. 7 lines 27-28);

a controller (figure 3, reference 14) configured to control the allocation of said communication resources among the links, the controller being separate and independent from the first station (col. 7 lines 31-32), based upon lengths of data queues in the first stations, wherein the information is a coded value (col. 9 lines 57-59) of the lengths of the data queues (col. 12 lines 6-8).

However, Yao et al. do not expressly disclose said allocation being performed in accordance with information transmitted from the first stations which indicates a need for communication resources. In an analogous art, Hwang et al. disclose said allocation being performed in accordance with information transmitted from the first stations which indicates a need for communication resources (figure 1, Abstract lines 14-16, and page 3, col. 4 lines 18-25).

One skilled in the art would have recognized said allocation being performed in accordance with information transmitted from the first stations which indicates a need for communication resources, and would have applied Hwang et al.'s mobile station transmission in Yao et al.'s determine the channel quality based on the length of queue 408. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention, to use Hwang et al.'s controlling asymmetric dynamic radio bearers in mobile packet data communications system in Yao et al.'s method and apparatus for voice latency reduction in a voice-over-data wireless communication system with the motivation being requested radio service (page 3, col. 4 line 20).

For claim 9, Yao et al. disclose wherein said controller (figure 3, reference 14) is part of said base station (figure 3, reference 12) (col. 7 lines 29-31).

For claim 10, Yao et al. disclose wherein said first stations are mobile stations in a wireless network (figure 3, reference 10, col. 7 line 28).

For claim 12, Yao et al. disclose wherein said base station includes a receiver configured to receive a transmission and producing data (col. 6 lines 7-8);

a decoder (figure 6, reference 614) configured to decode a field of said data and producing an indication of the data queue in an associated first station (figure 3, reference 10)(col. 13 line 54);

wherein said controller (figure 3, reference 14) receives said information from said decoder and allocates communication resources in accordance therewith (col. 7 lines 29-32).

For claim 13, Yao et al. disclose wherein said indication is provided for each data block transmitted (col. 12 lines 2-5).

For claim 17, Yao et al. disclose wherein the first stations transmit the indication to the controller in each data packet (col. 9 lines 57-59).

5. Claim 11 is rejected under 35 U.S.C. 103(a) as being unpatentable over Yao et al. (US 6,785,262) in view of Hwang et al. (EP 0981229 A2) further in view of Ishida et al. (US 6,975,604).

For claim 11, Yao et al. disclose:

a data queue (figure 4, reference 408, col. 9 line 18);

an encoder configured to generate a code representative of the length of the data queue (col. 9 line 17).

a transmitter (figure 4, reference 420) configured to transmit said data with said code included therein as a field (col. 9 lines 17-20).

However, Yao et al. in view of Hwang et al. do not expressly disclose a data generator. In an analogous art, Ishida et al. disclose a data generator (figure 6, reference 617);

One skilled in the art would have recognized the data generator, and would have applied Ishida et al.'s mobile station in Yao et al.'s determine the channel quality based on the length of queue 408. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention, to use Ishida et al.'s base station controller and mobile station in Yao et al.'s method and apparatus for voice latency reduction in a voice-over-data wireless communication system with the motivation being to generate data into frames (col. 8 lines 58-60).

6. Claims 14 and 18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yao et al. (US 6,785,262).

For claims 14 and 18, Yao et al. disclose method and apparatus for voice latency reduction in a voice-over-data wireless communication system, comprising:

- a receiver (figure 6, reference 602, col. 13 line 38); and

- a decoder (figure 6, reference 614) configured to decode a data queue in at least one mobile station (col. 13 lines 55-57); and

- a controller (figure 3, reference 14) configured to control allocation of communication resources (col. 7 line 32),

wherein said decoder (figure 6, reference 614) provides information for the at least one mobile station (figure 3, reference 10) to the controller (col. 7 lines 27-32).

However, Yao et al. do not expressly disclose decoding a code representative of a length of the data queue in at least one mobile station. To include the decoding a code representative of a length of a data queue in at least one mobile station would have been obvious to one of ordinary skill in the art because the decoder 614 would decode the data

frames generated by the voice encoder 406 based on the length of queue 408 (a code representative of a length of the data queue in at least one mobile station means).

7. Claims 15 and 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yao et al. (US 6,785,262) in view of Ishida et al. (US 6,975,604).

For claim 15, Yao et al. disclose method and apparatus for voice latency reduction in a voice-over-data wireless communication system, comprising:

a data queue, configure to receive data packets (figure 4, reference 408, col. 9 line 18);

an encoder (figure 4, reference 406) configured to encode a code (col. 9 lines 57-59) representative of the length of the data queue (col. 9 line 17, and col. 12 lines 6-13);
and

a transmitter (figure 4, reference 420) configured to transmit said data with said code included therein as a field (col. 9 lines 17-20).

However, Yao et al. do not expressly disclose a data generator. In an analogous art, Ishida et al. disclose a data generator (figure 6, reference 617);

One skilled in the art would have recognized the data generator, and would have applied Ishida et al.'s mobile station in Yao et al.'s determine the channel quality based on the length of queue 408. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention, to use Ishida et al.'s base station controller and mobile station in Yao et al.'s method and apparatus for voice latency reduction in a voice-over-data wireless communication system with the motivation being to generate data into frames (col. 8 lines 58-60).

Art Unit: 2616


For claim 19, Yao et al. disclose wherein the transmitter is further configured to transmit the indication in each data packet that is transmitted from the transmitter (col. 9 lines 17-20).

8. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Toan D. Nguyen whose telephone number is 571-272-3153. The examiner can normally be reached on M-F (7:00AM-4:30PM).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Mr. Huy Vu can be reached on 571-272-3155. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

TN
TN



HUY D. VU
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600